


AXN-M6T SERIES

265 – 315 WATT HIGH QUALITY MONO-CRYSTALLINE PV MODULES

AUXIN SOLAR[®]

Using automated production lines, top of the line solar cells and materials complying to highest industry standards, Auxin Solar provides a complete set of poly and mono-crystalline PV modules ranging from **10W to 315W**.

Auxin Solar offers panels for use in small off-grid systems to the largest on-grid solar farms. Panels are tested and qualified for the severest weather conditions.



FEATURES	BENEFITS
Solar cell efficiency over 18.6%	Generate more energy per square meter
Protective, Bypass diodes	Avoids effect of partial shading
Factory equipped weatherproof junction box Waterproof (UL94, V-O) connector Anodized aluminum frame 24v system	Flawless operation in wet weather and marine applications Perfect for GRID applications
White tempered glass EVA resin Weather proof film Anodized aluminum frame	Resilient to harsh weather conditions
Highest standards in manufacturing and design quality Cleanroom-like production line ISO9001:2008	Optimal panel performance Long term product performance

QUALITY ASSURANCE

-Backed by liability insurance
-Salt Mist Corrosion Certified
-Wind Resistance Load: 6000Pa
-ISO9001:2008

-Electrical insulation test
-Outdoor exposure test
-Hot spot endurance test
-UV exposure IEC61345
-Thermal cycling
-Humidity freeze
-Damp heat test
-Robustness of termination test
-Wet leakage current test
-Mechanical load test
-Hail impact test
-Bypass diode thermal test

INVESTMENT PROTECTION

- 5 years product workmanship guarantee
- 12 years 90% power output warranty
- 25 years 80% power output warranty




- Qualified, IEC 61215
- Safety tested, IEC 61730
- Periodic Inspection




Specifications subject to change without notice.

AXN-M6T SERIES


Electrical Characteristics	AXN-M6T265	AXN-M6T270	AXN-M6T275	AXN-M6T280	AXN-M6T285	AXN-M6T290	AXN-M6T295	AXN-M6T300	AXN-M6T305	AXN-M6T310	AXN-M6T315
Maximum Power [W]	265	270	275	280	285	290	295	300	305	310	315
Tolerance	± 3%										
Open circuit Voltage [V]	44.42	44.64	44.78	44.86	44.21	44.43	44.57	44.71	44.86	45.00	45.22
Short circuit Current [A]	8.11	8.14	8.18	8.21	8.39	8.48	8.52	8.58	8.72	8.79	8.89
Maximum Power Voltage [V]	36	36.21	36.58	36.86	36.72	36.72	36.72	36.72	36.72	36.72	36.72
Maximum Power Current [A]	7.36	7.44	7.52	7.60	7.77	7.9	8.04	8.17	8.31	8.45	8.58
Solar Cell Efficiency [%]	15.4	15.62	15.87	16.38	16.5	16.9	17.4	17.7	18.1	18.3	18.6
Series Fuse Rating [A]	15										
Terminal Box Protection Code	IP65										
Maximum System Voltage [V]	DC1000										
Operating Temperature [C]	-40 to 85										
Number of cells	72 (6" Mono)										




Front



Side



Back



Current & Voltage

Power & Voltage

Mechanical Characteristics	
Frame	Anodized Aluminum
Dimension (L x W x D)	77.20" x 39.17" x 1.97" / 1961mm x 995mm x 50mm
Weight/pc	24.0kg/52.9lbs
Packing	10pcs/carton
Loading/container	200pcs/20ft; 440/40ft
Maximum wind load	6000 Pa

Temperature Coefficients		Standard Test Conditions (STC)	
NOCT	48±0.1°C	Irradiance	1000W/m²
Short circuit current	+0.04%/C	Module Temperature	25 °C
Open circuit voltage	-0.35%/C	AM	1.5
Max power output	-0.45%/C		

Specifications subject to change without notice.

AUXIN SOLAR, 5891 Rue Ferrari, San Jose, CA 95138, USA
+1 408 868 4380(office), +1 408 868 4933(fax)

info@auxinsolar.com

www.auxinsolar.com



DC110512
©2012 AUXIN SOLAR
Printed in the USA