



SPECIFICATION OF 200W POLY SOLAR MODULE

Poly-Crystalline

Module type	Pm(W)	Number of cell	Cell Dimension (mm)	Max System Voltage(V)	Vm(V)	Im(A)	Voc(V)	Isc(A)
TYSM200	200W	54	156	1000	27	7.50	32.50	8.23

Parameter

Maximum system voltage (V)	1000
Temperature coefficients of Isc (%)	+0.1%/°C
Temperature coefficients of Voc (%)	-0.38%/°C
Temperature coefficients of Pm (%)	-0.47%/°C
Temperature coefficients of Im (%)	+0.1%/°C
Temperature coefficients of Vm (%)	-0.38%/°C
Temperature Range	-40°C ---85°C
Tolerance Wattage (e.g. +/-5%)	± 5%
Surface Maximum Load Capacity	60m/s (200kg/sq.m)
Junction Box Type	PPO, black
Connectors and Cables Type	4mm2
Length of Cables (mm)	900
Cell Efficiency (%)	>16.0%
Output tolerance (%)	± 5%
Frame (Material, Corners, etc.)	Anodized Aluminum Alloy
Standard Test Conditions	AM1.5 100MW/cm² 25°C
Guarantee of power	5 years for whole products,90% power for 10years, 80% power for 25years.
FF (%)	≥73.3%

Physical Characters

Output	Module Net Weight	Module Size (MM)	Packing	20' Container	40' Container
200W	19.0(kg)	990*1480*35	2pcs/carton	280 pcs	600 pcs



深圳市拓阳新能源科技有限公司

SHENZHEN TUOYANG NEW ENERGY CO.,LTD

Tel: +86-755-2305 5561 Mobile : +86-13717084860

www.sztuoyang.com

Email:szsyty@163.com