

Model	Pm Maximum power (Wp)	Voc Open circuit voltage (V)	Isc Short circuit current (A)	Vmp Optimum operating voltage(V)	Imp Optimum operating current(A)	Glass Dimension H × W×D (mm)	Module Dimension H × W×D (mm)	Length of Installati on Hole(H)	Crossed Space of Installati on Hole(W)	Diameter of Installation Hole
BD-280W-P	280	44.1	8.26	36	7.83	1955 × 988 × 3.2	1961 × 995 × 50	1400/700	945	6-14 × 9
BD-270W-P	270	43.8	8.09	35.4	7.63	1955 × 988 × 3.2	1961 × 995 × 50	1400/700	945	6-14 × 9
BD-260W-P	260	43.7	7.83	35	7.43	1955 × 988 × 3.2	1961 × 995 × 50	1400/700	945	6-14 × 9
BD-250W-P	250	43.5	7.54	34.7	7.2	1955 × 988 × 3.2	1961 × 995 × 50	1400/700	945	6-14 × 9
BD-230W-P	230	36.4	8.2	29.5	7.8	1640 × 988 × 3.2	1646 × 995 × 50	1000/500	945	6-14 × 9
BD-220W-P	220	36.2	7.97	29.5	7.61	1640 × 988 × 3.2	1646 × 995 × 50	1000/500	945	6-14 × 9
BD-210W-P	210	36	7.43	29.5	7.12	1640 × 988 × 3.2	1646 × 995 × 50	1000/500	945	6-14 × 9
BD-200W-P	200	36	7.06	29.5	6.78	1640 × 988 × 3.2	1646 × 995 × 50	1000/500	945	6-14 × 9
BD-190W-P	190	29.2	8.2	24	7.8	1324 × 988 × 3.2	1330 × 995 × 50	800/400	945	6- 14 × 9
BD-135W-P	135	21.6	7.95	18	7.22	1465 × 660 × 3.2	1471 × 666 × 35	1000/500	616	6- 14 × 9
BD-120W-P	120	21.6	7.34	18	6.67	1465 × 660 × 3.2	1471 × 666 × 35	1000/500	616	6- 14 × 9
BD-100W-P	100	21.6	6.05	18	5.55	1200 × 660 × 3.2	1206 × 666 × 35	800/400	615	6- 14 × 9
BD-80W-P	80	21.6	4.76	18	4.44	1200 × 529 × 3.2	1206 × 535 × 35	800/400	485	6- 14 × 9
BD-60W-P	60	21.6	3.57	18	3.33	974 × 529 × 3.2	980 × 535 × 35	765	485	4- 14 × 9
BD-50W-P	50	21.6	3.04	18	2.78	759 × 529 × 3.2	765 × 535 × 35	550	485	4- 14 × 9
BD-45W-P	45	21.6	2.72	18	2.5	660 × 529 × 3.2	666 × 535 × 25	460	500	4- 12 × 7
BD-40W-P	40	21.6	2.4	18	2.22	650 × 530 × 3.2	655 × 535 × 25	455	503	4- 12 × 7
BD-30W-P	30	21.6	1.82	18	1.67	660 × 414 × 3.2	666 × 420 × 25	455	374	4- 12 × 7
BD-20W-P	20	21.6	1.23	18	1.11	530 × 340 × 3.2	535 × 345 × 25	335	313	4- 12 × 7
BD-15W-P	15	21.5	0.92	18	0.83	400 × 340 × 3.2	405 × 345 × 25	280	313	4- 12 × 7
BD-10W-P	10	21.5	0.61	18	0.56	280 × 340 × 3.2	285 × 345 × 25	150	313	4- 12 × 7
BD-5W-P	5	21.5	0.3	18	0.28	280 × 180 × 3.2	285 × 185 × 25	150	150	4- 12 × 7
BD-3W-P	3	10.5	0.36	9	0.33	210 × 163 × 3.2	215 × 168 × 17	100	150	4-ø6.4
Operating temperature : - 40 °C to + 85 °C Maximum system voltage : >90V DC1000V; ≤90V DC 600V										
STC:Irradiance 1000W/ m ² , Temperature 25℃, AM=1.5V						Warranty : Pm is not less than 90% in 10years and 80% in 25 years				