

Mono-Crystalline Silicon Solar Module

| Item No. | NS-13W-1 |
|--|--|
| Mono or Poly | Mono |
| Maximum Power(Wp) | 13 |
| Maximum Power Voltage(Vmp) | 17.1 |
| Maximum Power Current (Imp) | 0.72 |
| Open circuit voltage(Voc) | 21.5 |
| Short circuit Current(Isc) | 0.78 |
| Size of module (mm) | 350*340*19mm |
| Weight(kgs) | 1.38 (without packaging) |
| Operating Temperature | -25°C~+65°C |
| Frame | Aluminium Frame |
| Power Tolerance | ±5% |
| Standard Test Conditions | AM1.5,1000W/m ² ,25°C |
| Laminate | Toughened glass +EVA+TPT |
| Front | High-transparent 3.2mm toughened glass |
| Back | TPT/TPE |
| Certification | ROHS |
| Lifetime | 15 years power output guarantee |
| No contact with strong corrosion substance. | |
| Please avoid the surface damage of hard stuff. | |
| No bending force during transportation and assemble. | |

NewSolar

NewSolar Energy Co., Ltd.

WuJiang Company

No.2518, Tongdingguoji, Huayuan Rd., Songling Zhen, Wujiang, Jiangsu, China

Tel: +86-512-63318199 Fax: +86-512-63421996

Taiwan Company

5F.-1, No.2, Sec. 4, Zhongyang Rd., Tucheng Dist., New Taipei City 236, Taiwan (R.O.C.)

Tel: +886-2-22691686 Fax: +886-2-22691985

