



常州嘉阳新能源科技有限公司

Changzhou Sunday Energy Co.,Ltd

Tel:+86 519 68081229 Website: www.sundayenergy.cn

Fax:+86 519 68081230 Email:sales@sundayenergy.cn

Add:No.888,Chengfeng Road,Jintan City,Jiangsu Province

SOLAR MODULE

SD-30P SD-35P

FEATURES

1. Low voltage-temperature coefficient enhances high-temperature operation.
2. Exceptional low-light performance and high sensitivity to light across the entire solar spectrum maximize yearly energy delivery.
3. 25-year limited warranty on power output, 2-year Limited warranty on materials and workmanship.

MATERIALS

1. Highest quality, high-transmission tempered glass provides enhanced stiffness and impact resistance.
2. Advanced EVA encapsulation system with triple-layer back sheet meets the most stringent safety requirements for high-voltage operation.
3. A sturdy, anodized aluminum frame allows modules to be easily roof-mounted with a variety of standard mounting systems.
4. Ultra reliable bypass diodes prevent damage through overheating due to shaded or defective cells.

BENEFITS

1. Manufactured in an ISO9001:2000 certified plant.
2. High efficiency, high safety, high reliability.
3. Output power tolerance of +/-3%.
4. CE、IEC、TUV、UL、MCS





常州嘉阳新能源科技有限公司

Changzhou Sunday Energy Co.,Ltd

Tel:+86 519 68081229 Website: www.sundayenergy.cn

Fax:+86 519 68081230 Email:sales@sundayenergy.cn

Add:No.888,Chengfeng Road,Jintan City,JIANGSU Province


ELECTRICAL SPECIFICATIONS

Model type	SD-30P	SD-35P
Peak power (Pmax)	30W	35W
Cell Efficiency	13.69%	15.97%
Module Efficiency	10.68%	12.46%
Maximum power voltage (Vmp)	17.30V	17.30V
Maximum power current (Imp)	1.75A	2.02A
Open circuit voltage (Voc)	21.30V	21.50V
Short circuit current (Isc)	2.01A	2.33A
Power Tolerance	-1 to +3%	
Maximum system voltage	DC 1000V	
Normal Operating Cell Temperature	45.3 ±2 °C	
Series fuse rating (A)	15A	
Number of bypass diode	3	

MECHANICAL SPECIFICATIONS

Cell type	156mm x 39mm
Number of cells	36 cells in series
Weight	3.2kg
Dimensions	780 x 360 x 28 mm
Max Load	5400Pascals (112 lb/ft ²)

PHYSICAL CHARACTERISTICS Unit:mm (inch)




TEMPERATURE COEFFICIENT


Temp. Coeff. of Isc (TK Isc)	0.065 %/°C
Temp. Coeff. of Voc (TK Voc)	-0.346 %/°C
Temp. Coeff. of Pmax (TK Pmax)	-0.46 %/°C

ELECTRICAL CHARACTERISTICS

Electrical performance (cell temperature:25°C)



Temperature dependence of Isc, Voc and Pmax



Irradiance dependence of Isc, Voc and Pmax (cell temperature:25°C)

