

# Photovoltaic Module

## Polycrystalline

### GS-70P



### Quality and Safety

- \*Rigorous quality control meeting the highest international standards
- \*High-transmissivity low-iron tempered glass, strong aluminium frame Using UV-resistant silicon
- \*IEC61215,IEC61730,Safety Class II,conformity to CE

### Features

- \*Aesthetic appearance with excellent efficiency based on innovative photovoltaic technologies
- \*High quality,strong aluminium frame,passing mechanical load testing 5400 Pa and wind pressure 2400Pa

### Warranties

- \*10 years limited product warranty
- \*15 years at90% of the minimal rated power output
- \*25 years at80% of the minimal rated power output

### Certificates



### Electrical Characteristics

Model	GS-70P
Maximum Power at STC (P <sub>max</sub> )	70W
Optimum Operating Voltage (V <sub>mp</sub> )	17.6V
Optimum Operating Current (I <sub>mp</sub> )	3.980A
Open-Circuit Voltage (V <sub>oc</sub> )	21.80V
Short-Circuit Current (I <sub>sc</sub> )	4.340A
Solar Cell Efficiency (%)	16.20
Solar Module Efficiency (%)	13.50
Operating Temperature	-40to85°C
Maximum System Voltage	DC1000
Maximum Series Fuse Rating	15A
Power Tolerance	+/-3%
STC:Irradiance 1000W/m <sup>2</sup> ,Modules Temperature 25°C,AM=1.5	

