

1500W Pure Sine Wave Inverters

FEATURES

True sine wave output (THD < 3%)
 RS-232 interface / Remote control port
 Input & output fully isolation
 Thermostatically control cooling fan
 Advanced microprocessor
 Output voltage & frequency switch selectable
 Input polarity reverse / under voltage / over voltage protections
 Output short circuit / overload / over temperature protections
 Built-in Voltage & Wattage meters & LED for power status
 UL / e-13 / CE / FCC approved





	MODEL No.	S1500-112	S1500-124	S1500-148	S1500-212	S1500-224	S1500-248
OUTPUT	AC VOLTAGE	100 / 110 / 120 VAC selectable by DIP switch			220 / 230 / 240 VAC selectable by DIP switch		
	RATED POWER	1500W					
	SURGE POWER	2000W					
	WAVEFORM	True sine wave (THD < 3%)					
	FREQUENCY	50 / 60 Hz selectable by DIP switch					
	AC REGULATION	± 3%					
	POWER FACTOR ALLOWED	COSθ-90° ~ COSθ+90°					
	STANDARD RECEPTACLES	NEMA5-15R / GFCI			Schuko / UK / Australia / universal		
INPUT	LED INDICATOR	OVP, UVP, OTP, OLPnput voltage level, output load level and fault status					
	NO LOAD CURRENT DRAW	0.87A	0.43A	0.23A	0.83A	0.43A	0.22A
	DC VOLTAGE	12VDC	24VDC	48VDC	12VDC	24VDC	48VDC
	VOLTAGE RANGE	10.5~15.0VDC	21.0~30.0VDC	42.0~60VDC	10.5~15.0VDC	21.0~30.0VDC	42.0~60VDC
	EFFICIENCY (Typ.)	87.0%	90.0%	92.0%	90.0%	93.0%	94.0%
	FUSE	35A x 2	20A x 2	10A x2	35A x 2	20A x 2	10A x2
PROTECTION	REMOTE CONTROL	CR5 optional					
	BAT. LOW ALARM	11VDC	22VDC	44VDC	11VDC	22VDC	44VDC
	BAT. LOW SHUTDOWN	10.5VDC	21.0VDC	42.0VDC	10.5VDC	21.0VDC	42.0VDC
	OVER LOAD	Shut off output voltage, re-power on to recover					
	OVER VOLTAGE	15.3VDC	30.6VDC	61.2VDC	15.3VDC	30.6VDC	61.2VDC
	OVER TEMPERATURE	Shut off output voltage, recovers automatically after temperature goes down					
ENVIRONMENT	OUTPUT SHORT	Shut off output voltage, re-power on to recover					
	BAT. POLARITY REVERSE	By fuse open					
	WORKING TEMP.	0 ~ +40°C					
	WORKING HUMIDITY	20% ~ 90% RH non-condensing					
SAFETY & EMC	STORAGE TEMP. & HUMIDITY	-30°C ~ +70°C / -22°F ~ +158°F / 10 ~ 95%					
	SAFETY STANDARDS	UL458 (only for "GFCI" receptacles)			-----		
	ISOLATION RESISTANCE	I/P ~ O/P: 100M Ohms / 500VDC					
	EMI CONDUCTION & RADIATION	Compliance to FCC classA			Compliance to En55022 class A		
	EMS IMMUNITY	-----			Compliance to EN61000-3 -2, 3		
	LVD	-----			Compliance to EN60950-1		
OTHERS	e-MARK	-----			Compliance to e-13 * 72/245/EEC, 95/54/EC		
	DIMENSION	390 x 275 x 105mm (L x W x H)					
	PACKING	7.0kgs; 2sets / 18kgs / CARTON					
	COOLING	Thermostatically controlled cooling fan					
	APPLICATION	Home and Office appliances, Power tools and Portable equipments, Vehicle, Yacht and Solar power systems ...etc.					




NEMA 5-15R




North America (GFCI)




Universal



Schuko



Australia
New Zealand



United Kingdom