

KS-600M 600Watt Modified Sine Wave Inverter



- ◆ Power on/off switch
- ◆USB connection (optimal)
- ◆Build in high Speed cooling fans
- ◆LED power / fault indicator
- ◆Fuse built out
- ◆Cigarette lighter and battery cables
- ◆One Years Warranty

Electrical Specifications

Continuous power 600 watts

Surge capacity (peak) 1200watts

DC Input (optional) 12 V;24VDC

Output wave form Modified sine wave

AC output frequency(optional) 50HZ/60 Hz

AC output voltage (optional) 220VAC/110 VAC

Optimum efficiency 85%

No load draw < 0.43 A

Input voltage range 10 - 15.5 VDC;20-30VDC

Over voltage shutdown 15+/-0.5 VDC;31+/-0.5 VDC

Low voltage alarm 10.5+/-0.5 VDC;21+/-0.5VDC

Under voltage shutdown 10.0+/-0.5 VDC;21+/-0.5 VDC

General Specifications

Working temperature (optimal) 15° C to 25° C (59° F to 77° F)

Working temperature -20° C to +40° C (-4° F to 104° F)

USB port(optimal) 5VDC, 500mA

LED indicator Power and fault status

Packing Details

Dimensions (L x W x H) $150 \times 105 \times 52 \text{ mm}$

Inverter Weight 1.25kgs Shipping Weight 20.5 kgs

Shipping Size 435 x 370 x370 mm

PCS/CTN 16PCS

Application: charge laptops, MP3 players, TVs, blenders and many other appliances and electronics.

TEL: 0086-574-22697100

Note:(1)Specifications are subject to change without notice

(2)Optional:Factory-Set