

## WVC-600 MICRO INVERTER



**WVC-600** micro inverter with Aluminum alloy shell & IP67 & waterproof streamline design, built-in high-performance Maximum Power Point Tracking (MPPT) function, more better to track change on solar luminosity and control different output power, effectively capture and collect sunlight. AC electric power transmission based on advanced reverse transmission technology which is one of our patented technologies, load priority and the rest electricity to the grid, high electricity transmission efficiency up to 99%. Excellent stability, reliability, safety and heat dissipation. Perfect communication solution of power line carrier technology between micro inverter and collector, RS232 serial port / WIFI wireless communication between collector and PC. Intelligent monitoring system, the collector is able to collect / track real-time data on each PV module and transmit to PC, user can easily control micro inverter's startup / shutdown / power regulation by software. Ingenious and modular connection accessories(cable and connector) for micro inverter cluster to ensure economy, easy installation and safety.



| High performance micro inverter  | Easy and afford to install  | Data transmission & communication  | Cost advantages  |
|--|---|--|--|
| <ul style="list-style-type: none"> <li>Input / output isolated to protect safety</li> <li>Rapid MPPT tracking technology</li> <li>Superior PV energy harvest</li> <li>Excellent thermal performance</li> <li>High overload capacity</li> </ul> | <ul style="list-style-type: none"> <li>Lightweight and compact size</li> <li>Outdoor application with firm IP67</li> <li>Ingenious and modular end connection</li> <li>Reverse connection prevention design</li> <li>Flexible installation</li> </ul> | <ul style="list-style-type: none"> <li>Intelligent remote monitoring system</li> <li>Real-time data for each PV module</li> <li>Power line carrier communication</li> <li>Wifi / RS232 serial communication</li> <li>LED indication implies system status</li> </ul> | <ul style="list-style-type: none"> <li>Wide input voltage for variety of modules</li> <li>Higher performance-to-price-ratio</li> <li>Low transport cost by small size design</li> <li>Low maintenance expense</li> </ul> |

| INPUT DATA                  | WVC-600 (120VAC / 230VAC)       |
|-----------------------------|---------------------------------|
| Recommended input power     | 500 watt - 600 watt             |
| Recommended PV modules      | 600W / Vmp, 34VDC < Voc < 50VDC |
| Maximum input DC voltage    | 50VDC                           |
| Peak power tracking voltage | 25VDC - 40VDC                   |
| Operating voltage range     | 17VDC - 50VDC                   |
| Min. / Max. Start voltage   | 22VDC - 50VDC                   |
| Maximum DC short current    | 40A                             |
| Maximum input current       | 25A                             |

| OUTPUT DATA                      | @120VAC             | @230VAC              |
|----------------------------------|---------------------|----------------------|
| Peak output power                | 600 watt            | 600 watt             |
| Rated output power               | 550 watt            | 550 watt             |
| Rated output current             | 4.58A               | 2.3A                 |
| Rated voltage range*             | 80VAC - 160VAC      | 180VAC - 260VAC      |
| Rated frequency range*           | 57 - 62.5Hz         | 47 - 52.5Hz          |
| Power factor (cos φ)             | >0.96               | >0.96                |
| Maximum units per branch circuit | 6pcs (Single phase) | 12pcs (Single phase) |

| OUTPUT EFFICIENCY         | @120VAC    | @230VAC    |
|---------------------------|------------|------------|
| Static MPPT efficiency    | 99.5%      | 99.5%      |
| Maximum output efficiency | 92.3%      | 94.6%      |
| Average efficiency        | 91.2%      | 93.1%      |
| Consumption at night      | <50mW Max. | <70mW Max. |
| THD                       | <5%        | <5%        |

| OPERATING CONDITIONS / DIMENSIONS / APPLICATIONS | WVC-600 (120VAC / 230VAC)                  |
|--|--|
| Environment temperature                          | -40°C ~ +60°C                              |
| Operating temperature (Inside inverter)          | -40°C ~ +82°C                              |
| Electrical isolation                             | Transformer                                |
| Cooling concept                                  | Self - cooling                             |
| Degree of protection (Waterproof)                | IP67                                       |
| Communication mode                               | Power line carrier, RS232, WiFi (optional) |
| Power transmission mode                          | Reverse transfer, load priority            |
| Dimensions (W×H×D mm)                            | 289mm × 200mm × 38mm                       |
| Net weight (Kg)                                  | 2.6Kg                                      |
| Electromagnetic compatibility                    | EN50081. PART 1, EN50082. PART 1           |
| Grid disturbance                                 | EN61000-3-2, Safety 62109                  |
| Grid detection                                   | DIN VDE 1026, UL1741                       |
| Certifications                                   | CEC, CE                                    |

\* AC rated voltage range and frequency range depend on local standards.

\* The monitoring software has ability to simultaneously run multiple thread of 6 units power line collectors and 600 units micro inverter.