



Leading Features

- ▶ Over 97.5% Max.efficiency
- ▶ Ultra wide input voltage range
- ▶ Dual MPPT design with precise MPPT algorithm
- ▶ Compact and light design for one-person easy installation
- ▶ IP65, visually pleasing for domestic environment
- ▶ RS 485, WiFi/GPRS (optional) interface
- ▶ Numerous protection functions
- ▶ WiFi and monitoring app available
- ▶ 5 years standard warranty, 10 years optional upgrade

Model		Solis-2.5K-2G
Input Side (DC)		
Max. input power		3kW
Max. input voltage		600V
Start-up input voltage		120V
MPPT voltage range		100-500V
Max. input current		10A+10A
MPPT number/Max. input strings number		2/2
Output Side (AC)		
Rated output power		2.5kW
Max. transient power		2.8kW
Rated grid voltage		220/230/240V
Grid voltage range		180~270V(adjustable)
Rated grid frequency		50/60Hz
Operating phase		Single
Max. output current		13.3A
Power factor		>0.99
Total harmonic distortion (THDi)		<3%
DC injection current		<20mA
Grid frequency range		47-52Hz or 57-62Hz(adjustable)
Efficiency		
Max. efficiency		97.5%
EU efficiency		96.8%
MPPT efficiency		99.9%
Protection		
DC reverse-polarity protection		Yes
Short circuit protection		Yes
Output over current protection		Yes
Output over voltage protection		Yes
Insulation resistance monitoring		Yes
Residual current detection		Yes
Surge protection		Yes
Grid monitoring		Yes
Islanding protection		Yes
Temperature protection		Yes
Integrated DC switch		Optional
General Data		
Dimensions		339W*565H*172.5D(mm)
Weight		14.5kg
Topology		Transformerless
Self consumption		<1W(Night)
Operating ambient temperature range		-25°C~60°C
Ingress protection		IP65
Noise emission(typical)		<30 dBA
Cooling concept		Natural convection
Max. operation altitude		2000m
Designed lifetime		>20 years
Grid connection standard		UL1741, G83/2, AS4777, VDE0126-1-1
Relative humidity		0~95%
Safety/EMC standard		EN61000-6-1:2007; EN61000-6-3:2007 IEC62109-1/2; AS3100
Features		
DC connection		MC-4 mateable
AC connection		IP67 rated plug
Display		LCD, 2 x 20 Z.
Interface		RS 485, WiFi/GPRS (optional)
Warranty		5~10 Years



Leading Features

- ▶ Over 97.5% Max.efficiency
- ▶ Ultra wide input voltage range
- ▶ Dual MPPT design with precise MPPT algorithm
- ▶ Compact and light design for one-person easy installation
- ▶ IP65, visually pleasing for domestic environment
- ▶ RS 485, WiFi/GPRS (optional) interface
- ▶ Numerous protection functions
- ▶ WiFi and monitoring app available
- ▶ 5 years standard warranty, 10 years optional upgrade

Model		Solis-2.5K-2G-ST
Input Side (DC)		
Max. input power		3kW
Max. input voltage		600V
Start-up input voltage		120V
MPPT voltage range		100-500V
Max. input current		10A
MPPT number/Max. input strings number		1/1
Output Side (AC)		
Rated output power		2.5kW
Max. transient power		2.8kW
Rated grid voltage		220/230/240V
Grid voltage range		180~270V(adjustable)
Rated grid frequency		50/60Hz
Operating phase		Single
Max. output current		13.3A
Power factor		>0.99
Total harmonic distortion (THDi)		<3%
DC injection current		<20mA
Grid frequency range		47-52Hz or 57-62Hz(adjustable)
Efficiency		
Max. efficiency		97.5%
EU efficiency		96.8%
MPPT efficiency		99.9%
Protection		
DC reverse-polarity protection		Yes
Short circuit protection		Yes
Output over current protection		Yes
Output over voltage protection		Yes
Insulation resistance monitoring		Yes
Residual current detection		Yes
Surge protection		Yes
Grid monitoring		Yes
Islanding protection		Yes
Temperature protection		Yes
Integrated DC switch		Optional
General Data		
Dimensions		339W*565H*172.5D(mm)
Weight		14.5kg
Topology		Transformerless
Self consumption		<1W(Night)
Operating ambient temperature range		-25°C~60°C
Ingress protection		IP65
Noise emission(typical)		<30 dBA
Cooling concept		Natural convection
Max. operation altitude		2000m
Designed lifetime		>20 years
Grid connection standard		UL1741, G83/2, AS4777, VDE0126-1-1
Relative humidity		0~95%
Safety/EMC standard		EN61000-6-1:2007; EN61000-6-3:2007 IEC62109-1/2; AS3100
Features		
DC connection		MC-4 mateable
AC connection		IP67 rated plug
Display		LCD, 2 x 20 Z.
Interface		RS 485, WiFi/GPRS (optional)
Warranty		5~10 Years



Leading Features

- ▶ Over 97.5% Max.efficiency
- ▶ Ultra wide input voltage range
- ▶ Dual MPPT design with precise MPPT algorithm
- ▶ Compact and light design for one-person easy installation
- ▶ IP65, visually pleasing for domestic environment
- ▶ RS 485, WiFi/GPRS (optional) interface
- ▶ Numerous protection functions
- ▶ WiFi and monitoring app available
- ▶ 5 years standard warranty, 10 years optional upgrade

Model		Solis-3.6K-2G
Input Side (DC)		
Max. input power		4.2kW
Max. input voltage		600V
Start-up input voltage		120V
MPPT voltage range		100-500V
Max. input current		10A+10A
MPPT number/Max. input strings number		2/2
Output Side (AC)		
Rated output power		3.6kW
Max. transient power		4kW
Rated grid voltage		220/230/240V
Grid voltage range		180~270V(adjustable)
Rated grid frequency		50/60Hz
Operating phase		Single
Max. output current		16A
Power factor		>0.99
Total harmonic distortion (THDi)		<3%
DC injection current		<20mA
Grid frequency range		47-52Hz or 57-62Hz(adjustable)
Efficiency		
Max. efficiency		97.5%
EU efficiency		96.8%
MPPT efficiency		99.9%
Protection		
DC reverse-polarity protection		Yes
Short circuit protection		Yes
Output over current protection		Yes
Output over voltage protection		Yes
Insulation resistance monitoring		Yes
Residual current detection		Yes
Surge protection		Yes
Grid monitoring		Yes
Islanding protection		Yes
Temperature protection		Yes
Integrated DC switch		Optional
General Data		
Dimensions		339W*565H*172.5D(mm)
Weight		14.5kg
Topology		Transformerless
Self consumption		<1W(Night)
Operating ambient temperature range		-25°C~60°C
Ingress protection		IP65
Noise emission(typical)		<30 dBA
Cooling concept		Natural convection
Max. operation altitude		2000m
Designed lifetime		>20 years
Grid connection standard		UL1741, G83/2, AS4777, VDE0126-1-1
Relative humidity		0~95%
Safety/EMC standard		EN61000-6-1:2007; EN61000-6-3:2007 IEC62109-1/2; AS3100
Features		
DC connection		MC-4 mateable
AC connection		IP67 rated plug
Display		LCD, 2 x 20 Z.
Interface		RS 485, WiFi/GPRS (optional)
Warranty		5~10 Years



Leading Features

- ▶ Over 97.5% Max.efficiency
- ▶ Ultra wide input voltage range
- ▶ Dual MPPT design with precise MPPT algorithm
- ▶ Compact and light design for one-person easy installation
- ▶ IP65, visually pleasing for domestic environment
- ▶ RS 485, WiFi/GPRS (optional) interface
- ▶ Numerous protection functions
- ▶ WiFi and monitoring app available
- ▶ 5 years standard warranty, 10 years optional upgrade

Model		Solis-3.6K-2G-ST
Input Side (DC)		
Max. input power		4.2kW
Max. input voltage		600V
Start-up input voltage		120V
MPPT voltage range		100-500V
Max. input current		18A
MPPT number/Max. input strings number		1/2
Output Side (AC)		
Rated output power		3.6kW
Max. transient power		4kW
Rated grid voltage		220/230/240V
Grid voltage range		180~270V(adjustable)
Rated grid frequency		50/60Hz
Operating phase		Single
Max. output current		16A
Power factor		>0.99
Total harmonic distortion (THDi)		<3%
DC injection current		<20mA
Grid frequency range		47-52Hz or 57-62Hz(adjustable)
Efficiency		
Max. efficiency		97.5%
EU efficiency		96.8%
MPPT efficiency		99.9%
Protection		
DC reverse-polarity protection		Yes
Short circuit protection		Yes
Output over current protection		Yes
Output over voltage protection		Yes
Insulation resistance monitoring		Yes
Residual current detection		Yes
Surge protection		Yes
Grid monitoring		Yes
Islanding protection		Yes
Temperature protection		Yes
Integrated DC switch		Optional
General Data		
Dimensions		339W*565H*172.5D(mm)
Weight		14.5kg
Topology		Transformerless
Self consumption		<1W(Night)
Operating ambient temperature range		-25°C~60°C
Ingress protection		IP65
Noise emission(typical)		<30 dBA
Cooling concept		Natural convection
Max. operation altitude		2000m
Designed lifetime		>20 years
Grid connection standard		UL1741, G83/2, AS4777, VDE0126-1-1
Relative humidity		0~95%
Safety/EMC standard		EN61000-6-1:2007; EN61000-6-3:2007 IEC62109-1/2; AS3100
Features		
DC connection		MC-4 mateable
AC connection		IP67 rated plug
Display		LCD, 2 x 20 Z.
Interface		RS 485, WiFi/GPRS (optional)
Warranty		5~10 Years



Leading Features

- ▶ Over 97.5% Max.efficiency
- ▶ Ultra wide input voltage range
- ▶ Dual MPPT design with precise MPPT algorithm
- ▶ Compact and light design for one-person easy installation
- ▶ IP65, visually pleasing for domestic environment
- ▶ RS 485, WiFi/GPRS (optional) interface
- ▶ Numerous protection functions
- ▶ WiFi and monitoring app available
- ▶ 5 years standard warranty, 10 years optional upgrade

Model		Solis-3K-2G
Input Side (DC)		
Max. input power		3.5kW
Max. input voltage		600V
Start-up input voltage		120V
MPPT voltage range		100-500V
Max. input current		10A+10A
MPPT number/Max. input strings number		2/2
Output Side (AC)		
Rated output power		3kW
Max. transient power		3.3kW
Rated grid voltage		220/230/240V
Grid voltage range		180~270V(adjustable)
Rated grid frequency		50/60Hz
Operating phase		Single
Max. output current		15.7A
Power factor		>0.99
Total harmonic distortion (THDi)		<3%
DC injection current		<20mA
Grid frequency range		47-52Hz or 57-62Hz(adjustable)
Efficiency		
Max. efficiency		97.5%
EU efficiency		96.8%
MPPT efficiency		99.9%
Protection		
DC reverse-polarity protection		Yes
Short circuit protection		Yes
Output over current protection		Yes
Output over voltage protection		Yes
Insulation resistance monitoring		Yes
Residual current detection		Yes
Surge protection		Yes
Grid monitoring		Yes
Islanding protection		Yes
Temperature protection		Yes
Integrated DC switch		Optional
General Data		
Dimensions		339W*565H*172.5D(mm)
Weight		14.5kg
Topology		Transformerless
Self consumption		<1W(Night)
Operating ambient temperature range		-25°C~60°C
Ingress protection		IP65
Noise emission(typical)		<30 dBA
Cooling concept		Natural convection
Max. operation altitude		2000m
Designed lifetime		>20 years
Grid connection standard		UL1741, G83/2, AS4777, VDE0126-1-1
Relative humidity		0~95%
Safety/EMC standard		EN61000-6-1:2007; EN61000-6-3:2007 IEC62109-1/2; AS3100
Features		
DC connection		MC-4 mateable
AC connection		IP67 rated plug
Display		LCD, 2 x 20 Z.
Interface		RS 485, WiFi/GPRS (optional)
Warranty		5~10 Years



Leading Features

- ▶ Over 97.5% Max.efficiency
- ▶ Ultra wide input voltage range
- ▶ Dual MPPT design with precise MPPT algorithm
- ▶ Compact and light design for one-person easy installation
- ▶ IP65, visually pleasing for domestic environment
- ▶ RS 485, WiFi/GPRS (optional) interface
- ▶ Numerous protection functions
- ▶ WiFi and monitoring app available
- ▶ 5 years standard warranty, 10 years optional upgrade

Model		Solis-3K-2G-ST
Input Side (DC)		
Max. input power		3.5kW
Max. input voltage		600V
Start-up input voltage		120V
MPPT voltage range		100-500V
Max. input current		18A
MPPT number/Max. input strings number		1/2
Output Side (AC)		
Rated output power		3kW
Max. transient power		3.3kW
Rated grid voltage		220/230/240V
Grid voltage range		180~270V(adjustable)
Rated grid frequency		50/60Hz
Operating phase		Single
Max. output current		15.7A
Power factor		>0.99
Total harmonic distortion (THDi)		<3%
DC injection current		<20mA
Grid frequency range		47-52Hz or 57-62Hz(adjustable)
Efficiency		
Max. efficiency		97.5%
EU efficiency		96.8%
MPPT efficiency		99.9%
Protection		
DC reverse-polarity protection		Yes
Short circuit protection		Yes
Output over current protection		Yes
Output over voltage protection		Yes
Insulation resistance monitoring		Yes
Residual current detection		Yes
Surge protection		Yes
Grid monitoring		Yes
Islanding protection		Yes
Temperature protection		Yes
Integrated DC switch		Optional
General Data		
Dimensions		339W*565H*172.5D(mm)
Weight		14.5kg
Topology		Transformerless
Self consumption		<1W(Night)
Operating ambient temperature range		-25°C~60°C
Ingress protection		IP65
Noise emission(typical)		<30 dBA
Cooling concept		Natural convection
Max. operation altitude		2000m
Designed lifetime		>20 years
Grid connection standard		UL1741, G83/2, AS4777, VDE0126-1-1
Relative humidity		0~95%
Safety/EMC standard		EN61000-6-1:2007; EN61000-6-3:2007 IEC62109-1/2; AS3100
Features		
DC connection		MC-4 mateable
AC connection		IP67 rated plug
Display		LCD, 2 x 20 Z.
Interface		RS 485, WiFi/GPRS (optional)
Warranty		5~10 Years



Leading Features

- ▶ Over 97.8% Max.efficiency
- ▶ Ultra wide input voltage range
- ▶ Dual MPPT design with precise MPPT algorithm
- ▶ Compact and light design for one-person easy installation
- ▶ IP65, visually pleasing for domestic environment
- ▶ RS 485, WiFi/GPRS (optional) interface
- ▶ Numerous protection functions
- ▶ WiFi and monitoring app available
- ▶ 5 years standard warranty, 10 years optional upgrade

Model		Solis-4.6K-2G
Input Side (DC)		
Max. input power		5.3kW
Max. input voltage		600V
Start-up input voltage		120V
MPPT voltage range		100-500V
Max. input current		15A+15A
MPPT number/Max. input strings number		2/2
Output Side (AC)		
Rated output power		4.6kW
Max. transient power		5kW
Rated grid voltage		220/230/240V
Grid voltage range		180~270V(adjustable)
Rated grid frequency		50/60Hz
Operating phase		Single
Max. output current		23.8A
Power factor		>0.99
Total harmonic distortion (THDi)		<3%
DC injection current		<20mA
Grid frequency range		47-52Hz or 57-62Hz(adjustable)
Efficiency		
Max. efficiency		97.8%
EU efficiency		97%
MPPT efficiency		99.9%
Protection		
DC reverse-polarity protection		Yes
Short circuit protection		Yes
Output over current protection		Yes
Output over voltage protection		Yes
Insulation resistance monitoring		Yes
Residual current detection		Yes
Surge protection		Yes
Grid monitoring		Yes
Islanding protection		Yes
Temperature protection		Yes
Integrated DC switch		Optional
General Data		
Dimensions		339W*565H*172.5D(mm)
Weight		16.5kg
Topology		Transformerless
Self consumption		<1W(Night)
Operating ambient temperature range		-25°C~60°C
Ingress protection		IP65
Noise emission(typical)		<30 dBA
Cooling concept		Natural convection
Max. operation altitude		2000m
Designed lifetime		>20 years
Grid connection standard		UL1741, G59/3, AS4777, VDE0126-1-1
Relative humidity		0~95%
Safety/EMC standard		EN61000-6-1:2007; EN61000-6-3:2007 IEC62109-1/2; AS3100
Features		
DC connection		MC-4 mateable
AC connection		IP67 rated plug
Display		LCD, 2 x 20 Z.
Interface		RS 485, WiFi/GPRS (optional)
Warranty		5~10 Years



Leading Features

- ▶ Over 97.8% Max.efficiency
- ▶ Ultra wide input voltage range
- ▶ Dual MPPT design with precise MPPT algorithm
- ▶ Compact and light design for one-person easy installation
- ▶ IP65, visually pleasing for domestic environment
- ▶ RS 485, WiFi/GPRS (optional) interface
- ▶ Numerous protection functions
- ▶ WiFi and monitoring app available
- ▶ 5 years standard warranty, 10 years optional upgrade

Model		Solis-4K-2G
Input Side (DC)		
Max. input power		4.6kW
Max. input voltage		600V
Start-up input voltage		120V
MPPT voltage range		100-500V
Max. input current		15A+15A
MPPT number/Max. input strings number		2/2
Output Side (AC)		
Rated output power		4kW
Max. transient power		4.4kW
Rated grid voltage		220/230/240V
Grid voltage range		180~270V(adjustable)
Rated grid frequency		50/60Hz
Operating phase		Single
Max. output current		21A
Power factor		>0.99
Total harmonic distortion (THDi)		<3%
DC injection current		<20mA
Grid frequency range		47-52Hz or 57-62Hz(adjustable)
Efficiency		
Max. efficiency		97.8%
EU efficiency		97%
MPPT efficiency		99.9%
Protection		
DC reverse-polarity protection		Yes
Short circuit protection		Yes
Output over current protection		Yes
Output over voltage protection		Yes
Insulation resistance monitoring		Yes
Residual current detection		Yes
Surge protection		Yes
Grid monitoring		Yes
Islanding protection		Yes
Temperature protection		Yes
Integrated DC switch		Optional
General Data		
Dimensions		339W*565H*172.5D(mm)
Weight		14.5kg
Topology		Transformerless
Self consumption		<1W(Night)
Operating ambient temperature range		-25°C~60°C
Ingress protection		IP65
Noise emission(typical)		<30 dBA
Cooling concept		Natural convection
Max. operation altitude		2000m
Designed lifetime		>20 years
Grid connection standard		UL1741, G59/3, AS4777, VDE0126-1-1
Relative humidity		0~95%
Safety/EMC standard		EN61000-6-1:2007; EN61000-6-3:2007 IEC62109-1/2; AS3100
Features		
DC connection		MC-4 mateable
AC connection		IP67 rated plug
Display		LCD, 2 x 20 Z.
Interface		RS 485, WiFi/GPRS (optional)
Warranty		5~10 Years



Leading Features

- ▶ Over 97.8% Max.efficiency
- ▶ Ultra wide input voltage range
- ▶ Dual MPPT design with precise MPPT algorithm
- ▶ Compact and light design for one-person easy installation
- ▶ IP65, visually pleasing for domestic environment
- ▶ RS 485, WiFi/GPRS (optional) interface
- ▶ Numerous protection functions
- ▶ WiFi and monitoring app available
- ▶ 5 years standard warranty, 10 years optional upgrade

Model		Solis-5K-2G
Input Side (DC)		
Max. input power		5.8kW
Max. input voltage		600V
Start-up input voltage		120V
MPPT voltage range		100-500V
Max. input current		15A+15A
MPPT number/Max. input strings number		2/2
Output Side (AC)		
Rated output power		5kW
Max. transient power		5kW
Rated grid voltage		220/230/240V
Grid voltage range		180~270V(adjustable)
Rated grid frequency		50/60Hz
Operating phase		Single
Max. output current		23.8A
Power factor		>0.99
Total harmonic distortion (THDi)		<3%
DC injection current		<20mA
Grid frequency range		47-52Hz or 57-62Hz(adjustable)
Efficiency		
Max. efficiency		97.8%
EU efficiency		97%
MPPT efficiency		99.9%
Protection		
DC reverse-polarity protection		Yes
Short circuit protection		Yes
Output over current protection		Yes
Output over voltage protection		Yes
Insulation resistance monitoring		Yes
Residual current detection		Yes
Surge protection		Yes
Grid monitoring		Yes
Islanding protection		Yes
Temperature protection		Yes
Integrated DC switch		Optional
General Data		
Dimensions		339W*565H*172.5D(mm)
Weight		16.5kg
Topology		Transformerless
Self consumption		<1W(Night)
Operating ambient temperature range		-25°C~60°C
Ingress protection		IP65
Noise emission(typical)		<30 dBA
Cooling concept		Natural convection
Max. operation altitude		2000m
Designed lifetime		>20 years
Grid connection standard		UL1741, G59/3, AS4777, VDE0126-1-1
Relative humidity		0~95%
Safety/EMC standard		EN61000-6-1:2007; EN61000-6-3:2007 IEC62109-1/2; AS3100
Features		
DC connection		MC-4 mateable
AC connection		IP67 rated plug
Display		LCD, 2 x 20 Z.
Interface		RS 485, WiFi/GPRS (optional)
Warranty		5~10 Years