

Model	YDZ-8000W			
Output power	8000W			
Peak power	16000W			
Input voltage	DC24V	DC48V	DC24V	DC48V
Output voltage	100VAC or 110VAC or 120VAC ±5%		220VAC or 230VAC or 240VAC ±5%	
No-load current (less-than)	1.5A	0.9A	1.5A	0.9A
Output frequency	50HZ±0.5HZ or 60HZ±0.5HZ			
Output wave	Pure sine wave			
Waveform Distortion	THD<3%(linear load)			
USB	5V 1000MA			
Max. working efficiency	94.80%			
Input voltage range	19.8–30.27V	40.2–60.4V	19.8–30.27V	40.2–60.4V
Operating temperature range	- 10° – +50°			
Storage temperature	- 30° – +70°			
Humidity	Max. 90%, non-condensing			
Warranty	Two years			
Dimensions (W*H*D)	625*240*190mm			
Package size	660*260*220mm			
Net weight/Gross weight	14kg			
Starting	bipolar soft start			
Low voltage alarm	21V±0.5V	42V±1V	21V±0.5V	42V±1V
Low voltage shut down	20V±0.5V	40V±1V	20V±0.5V	40V±1V
Low voltage recovery	24V±0.5V	48V±1V	24V±0.5V	48V±1V
Over voltage shut down	31V±0.5V	61V±1V	31V±0.5V	61V±1V
Over voltage recovery	29.5V±0.5V	59V±1V	29.5±0.5V	59V±1V
LED Lights	Blue indicator light (inverter output, normal operation); the red indicator flashes (under / over voltage, overload, temperature, short circuit)			
Protection	Battery over under / over voltage, overload, temperature, AC short circuit protection (positive and negative polarity protection)			
Fuse	DC short circuit protection			
Display	LED high-definition digital display			
Circuit Topology	Frequency link			
Cooling way	Intelligent cooling, built-in cooling block			